

Daylighting Models

Integrated Design Lab
The IDL is devoted to the development of high performance buildings in the international world with emphasis on energy efficiency, building systems and the integration of human factors.

Jake Dunn* as Alvar Aalto

*Now Principal at ZGF, Portland

1

You need three things:

Model "light-tight and big enough"	
Sky "clear or cloudy... real or not"	
Sensor "eye, camera, or meter"	

2

Real Skies...

The real sky...perfectly cloudy or perfectly clear...

Eden Project
Grimshaw

3

Artificial Skies...






Figure 9. Schematic of 24-ft diameter sky simulator with model on platform. (XBL 8412-5328)

4



5




6




The Bartlett School
New sky at Here East

7



8




9



10




11



12



13



14

Why is a daylighted artificial sky desirable?

Three reasons—

- **Philosophical:** Is there a passive tool that could encourage this mindset and be used to test daylighting models?
- **Qualitative:** Could natural light be used for model testing?
- **Environmental:** Is there a zero-energy alternative to electrically lighted artificial skies?

15

Design Goal

8:00am 10:00am 12:00pm 2:00pm 4:00pm

180° fisheye view for perfect overcast. Simulation for 21 Sept, Seattle, WA.
Integrated Design Lab | University of Washington | Seattle, WA

The brightness of even the ideal overcast sky varies significantly during each day.

However, the distribution of light is constant—3x brighter at the zenith.

So, our goal is to provide proper distribution, not specific luminance.

16

**Experiment:
Build some models...**

17

YES!


IDL Skybox Prototype Skybox

Zero watts total!


18



19



20



21

NSF Daylighting
Model Data Record Sheet

Condition: Artificial
Sec: 00
Chart: C2.A.A.
VENUE: 5

Notes:
MINIMUM LIGHTING
SCHEDULED LIGHTING

Section: [Diagram showing a cross-section of a building with light sources and interior levels.]
Plan: [Diagram showing a floor plan with numbered zones.]

EXTERIOR	INTERIOR DAYLIGHT (Q PD)											
SCIP	1	2	3	4	5	6	7	8	9	10	11	12
FC	100	100	100	100	100	100	100	100	100	100	100	100
CU	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

Figure IV.E.1 - A "visual lab" set up (w/ seats from Michigan center)

1. Video monitor (Panasonic CT-1930)
2. battery and power supply (Panasonic NV-858)
3. tape player (Panasonic NV-820)
4. video camera (Panasonic WV-2400)
5. control camera (Hitachi HV-9017)
6. color camera (Hitachi HV-9017)
7. video recorder (Sony BV-1900 Beta)
8. Video monitor (Sony KV-131CR)
9. Video recorder (RCA VHS)
10. movie camera (RCA VHS)
11. computer terminal (Macintosh)
12. computer printer (MacPrinter)
13. computer terminal (IBM XT)
14. acoustic noise recorder

22

Cameras


Musée d'Orsay, Paris and model

23


Physical Models...

...ugly on the outside!

24



25




26



27



28




29




30



31




32




33



34




35




36




37




38



39



40



41



42
