



## Interveners

## •Transmitters

• Specular

• Semi


• Diffuse

## •Reflectors


• Specular

- Semi
- Diffuse































































25




Photo @ James Newton

 All light should have a clear purpose: Before installing or replacing a light, determine if it is needed and consider how it will impact the area, taking into account wildlife, nature and sustainability. In some instances, reflective paint or self-luminous markers for signs, curbs, and steps might reduce the need for permanently installed illumination.

- Light should be directed only where needed: Use shielding and careful aiming to direct a light beam so that it points downward and does not spill.
- Light should be no brighter than necessary: Use the lowest light level required and be mindful of surface conditions as some surfaces reflect light into the night sky.
- Light should be used only when useful: Use controls to ensure that light is available when needed, dimmed or turned off when possible.
- Use warmer color temperatures: Limit the amount of shorter wavelength (blue-violet) light, which some consider to be harmful.

--IES & Int'l Dark Sky Assn

26





There is a logarithmic relationship between senders
and receiversbetween subjective and objective

Equally perceived intervals of sensation	Corresponding quantity of stimulus
1	10 or 10 <sup>1</sup>
2	100 or 10 <sup>2</sup>
3	1,000 or 10 <sup>3</sup>
4	10,000 or 10 <sup>4</sup>
5	100,000 or 10 <sup>5</sup>

Therefore, 5x the sensation requires 10<sup>5</sup> the stimulus



